



Product overview

The AX-LCD-1 range of units feature a high-contrast, blue backlit liquid crystal display with white text. Various options are available such that the 0-10V input can be used to display a variety of ranges and units of measurement. (Please advise when ordering). The displays fit a standard single gang back-box.

Features

- Blue LCD Display with 19mm height characters
- 0-10V input range
- Fits standard single gang deep back box
- 24Vac or dc supply

Product specifications

Power Supply		24Vac at 15mA
		24Vdc at 30mA
Input		0-10Vdc, 1mA maximum
Display		Blue LCD Display with 20mm height characters
Scaling	Temperature	0°C to 50.0°C
	Pressure	-99 to 99 Pa
	Relative Humidity	0 to 99.9% RH
Finish (Plate)		Brushed Stainless Steel
Weight & Dimensions		250gms (approx) 86 x 86 x 40mm (approx)
Backbox Depth		45mm
Ambient Temperature		0°C to 60°C
Country of Origin		United Kingdom

Order codes

AX-LCD-1-T	Room temperature display
AX-LCD-1-P	Room pressure display
AX-LCD-1-RH	Room relative humidity display

ANNICOM Ltd

Unit 21 Highview, High Street, Bordon, Hampshire. GU35 0AX

Tel: +44 (0)1420 487788 Fax: +44 (0)1420 487799

Email: sales@annicom.com Website: www.annicom.com

Datasheet contents

Every effort has been taken in the production of this data sheet to ensure accuracy. Annicom do not accept responsibility for any damage, expense, injury, loss or consequential loss resulting from any errors or omissions. Annicom has a policy of continuous improvement and reserves the right to change this specification without notice.

Installation

The AX-LCD-1 should be installed by a suitably qualified technician in conjunction with any guidelines for the equipment it is to be connected to and any local regulations. Field wiring should be installed to satisfy the requirements set out by the manufacturer of the equipment that the module is being connected to.

Connections

