SI-TX-D12L 230Vac to 24Vac 12VA DIN rail Transformer





Product overview

The SI-TX-D12L is a 230/24Vac encapsulated transformer supplied ready for DIN rail mounting. Fuses are incorporated on both the input and output connections.

Features

- 12VA rating
- Rising clamp terminal blocks
- Integral fuses on input and output connections
- DIN rail mounting Enclosure

Product specifications

Output Rating:	12VA
Input:	230Vac
Output Supply:	24Vac
Typical Regulation:	18%
Input Fuse (20mm Antisurge):	250mA, 250V
Output Fuse (20mm Antisurge):	1A
Dimensions:	105 x 91 x 52mm
Weight:	750 gms
Electrical Connections:	Rising clamp terminals for 0.5-2.5mm ² Cable
Ambient Temperature Range:	-10 to +50°C
Country of Origin:	United Kingdom

Order codes


SI-TX-D12L

230Vac to 24Vac Transformer 12VA - DIN rail mount - Low profile

Installation

The SI-TX-D12L transformers should be installed by a suitably qualified technician in conjunction with any guidelines for the equipment it is to be connected to and any local regulations. Field wiring should be installed to satisfy the requirements set out by the manufacturer of the equipment that the module is being connected to.

Connections and Mounting



Every effort has been taken in the production of this data sheet to ensure accuracy. Axio do not accept responsibility for any damage, expense, injury, loss or consequential loss resulting from any errors or omissions. Axio has a policy of continuous improvement and reserves the right to change this specification without notice.

Issue 1 (7/6/17)

© Copyright Annicom 2017. All Rights Reserved

Annicom Ltd Unit 21, Highview, Bordon, Hampshire. GU35 0AX Tel: +44 (0)1420 487788 Fax: +44 (0)1420 487799 Email: sales@annicom.com Website: www.annicom.com